

6-FM-134

The Narada Telecom range of VRLA batteries are well suited to provide battery backup to any application long duration or outside plant application.

All Narada Telecom series batteries use optimized plate technology and a patented post design offering exceptional service life.



Technical Features:

- ◆ Flame Retardant ABS Cover and Container, UL94 V-0, LOI>28%
- ◆ Patented copper alloy terminal design
- ◆ Epoxy TPS design for high reliability post seal
- ◆ 6 months of storage at 77°F (25°C) with a capacity > 80%
- ◆ Initial capacity at 100%
- ◆ Low pressure one-way flame arresting valve(s) UL1989
- ◆ Absorbent Glass Mat (AGM) Sealed Technology, Recombination efficiency of 99.9%

Compliance and Safety:

- ◆ **ISO 9001:2000 and ISO 14001:2004 certified production facilities**
- ◆ UL Recognized Component 924, for use in or with listed UL1778, UL1989 and UL924 systems
- ◆ IEC60896-21/22
- ◆ BS6290 part 4 / Eurobatt guide
- ◆ **TL9001 / ISO9001(TUV) Quality System**
- ◆ Battery installation compliant with: EN 50272-2
- ◆ All batteries meet or exceed IEEE recommended practices

Transportation:

- ◆ Classified as Nonspillable UN 2800 and meet the Nonspillable criteria listed in DOT-CFR Title 49, 171-189 (d) (3) (i) and (ii) and exempt from CFR 49, Subchapter C requirements
- ◆ Meets transportation conditions of IMDG exemption 238, IATA/ICAO Special Provision A67 (Not Restricted)

Ah @ 8hr 1.75 vpc / 77°F (25°C)	131.4 Ah
Ah @ 10hr 1.80 vpc / 77°F (25°C)	134 Ah

Nominal Voltage	12V
Float Charge Voltage @25°C (2.23 – 2.27vpc)	13.4 – 13.6
Max. Charge Current (A) (5 hour rate @ 1.75vpc)	33.5 Amps

Electrolyte Absorbed H ₂ SO ₄	1.300
--	-------

Short Circuit Current (A)	3077 Amps
Internal Resistance (mΩ)	3.7

Terminal Type	Torque
M6-F (Top Insert)	78 in-lbs (8 ±1 Nm)

Dimension	in	mm
Length	13.59	345
Length Base	13.59	345
Width	6.78	172
Overall Height	11.26	286

	Lbs.	Kg
Weight	96	43.5

CLEI	Pending	CPR	Pending
------	---------	-----	---------

Operating Parameters

Float Charging Voltage	13.5V / 2.25vpc @ 77°F (25°C)
Equalize /Cycle	14.0V – 14.3V 2.33Vpc to 2.38Vpc @ 77°F (25°C)
See Operations and Maintenance Manual for specific guidelines and recharge times	

Charging Temperature Compensation	-2 mV/cell/°F > 77°F (-3.6 mV/cell /°C > 25°C)
	+2 mV/cell/°F < 77°F (+3.6 mV/cell/°C < 25°C)

Maximum AC Ripple (Charger)	0.5% RMS, 1.5% peak-to-peak for float charge voltage for best results
-----------------------------	---

Operating Temperature Range	
Nominal	+74°F (24°C) to 80°F (27°C)
Charge	-20°F (-28°C) to +122°F (50°C)
Discharge	-40°F (-40°C) to +140°F (60°C)
Storage Temperature Range	-4°F (-20°C) to +104°F (40°C)

Constant Current Discharge (Amps) @ 77°F/25°C															
End vpc	5m	15m	30m	45m	1h	2h	3h	4h	5h	6h	8h	10h	12h	20h	24h
1.67	409	225	139	102	82.6	47.3	36.7	28.5	25.5	21.5	16.6	13.7	11.6	7.22	6.03
1.70	404	223	138	101	81.9	47.1	36.5	28.3	25.3	21.4	16.6	13.6	11.5	7.20	6.03
1.75	372	215	136	101	80.8	45.8	36.1	28.1	24.9	21.3	16.4	13.5	11.5	7.20	6.03
1.80	333	200	131	96.4	78.7	45.4	35.9	27.9	24.2	20.9	16.3	13.4	11.4	7.10	6.01
1.83	318	184	128	93.4	75.2	45.0	34.6	26.6	23.6	20.2	15.9	12.9	10.9	7.10	5.92
1.85	298	178	119	89.5	73.1	43.2	33.7	26.4	22.9	19.8	15.4	12.8	10.9	6.96	5.88
1.86	289	175	114	87.5	72.0	42.4	33.3	26.2	22.6	19.5	15.2	12.7	10.8	6.88	5.86

Constant Power Discharge (Watt/Cell) @ 77°F/25°C															
End vpc	5m	15m	30m	45m	1h	2h	3h	4h	5h	6h	8h	10h	12h	20h	24h
1.67	797	438	272	199	161	92.2	71.6	55.6	49.7	41.9	32.3	26.8	22.7	14.1	11.8
1.70	788	434	268	198	160	91.8	71.2	55.2	49.3	41.7	32.3	26.6	22.4	14.0	11.8
1.75	725	419	266	196	158	89.3	70.4	54.8	48.5	41.6	32.0	26.4	22.4	14.0	11.8
1.80	649	391	254	188	153	88.5	70.0	54.4	47.2	40.8	31.8	26.1	22.2	13.8	11.7
1.83	620	358	249	182	147	87.8	67.4	51.8	45.9	39.4	31.0	25.2	21.3	13.8	11.5
1.85	582	347	232	175	143	84.2	65.8	51.4	44.7	38.5	30.0	24.9	21.2	13.6	11.5
1.86	563	341	223	171	140	82.7	64.9	51.0	44.1	38.1	29.6	24.8	21.1	13.4	11.4

China: **Narada**
 NARADA POWER SOURCE CO.,LTD.
 No.459 Wensan Road, Hangzhou, Zhejiang, P.R.China
 Tel:+86-571-28827013 Fax:+86-571-85126942
 Website:www.en.naradabattery.com E-mail: intl@narada.biz

MPI Narada MPI-Narada
 44 Oak St
 Newton, MA 02464
 Tel: 800-982-4339
 sales@mpinarada.com www.mpinarada.com

